# No Rot, No Painting, No Worries!

# Why Aluminum?



Use aluminum cladding to make your peeling, rotted door frame look better than new and keep that look permanently!

No Painting . . . EVER! No Cracking or Peeling Dark Colors Available Heavy Duty - Resists Dents No Exposed Fasteners Storm Door Ready

### **CLADDING SPECIFICATIONS**

Aluminum Thickness: .062, 16 gauge, 1/16" Brickmould: Matches #180 Wood Style

# Remodel Clad System





1100 S Huron Rd, Green Bay, WI 54311 | 920-393-1340 www.frontlinebldg.com | orders@frontline.bldg.com

Patent No. US 7,111,433B2 | US 7,454,865B2 | CA 2,415,545

DISTRIBUTED BY:

# ALUMINUM FRAMES FOR ENTRY & GARAGE DOORS

FOR REMODELING APPLICATIONS. APPLIED OVER EXISTING JAMBS!



## MAKE YOUR FRAMES BETTER THAN NEW!



/RMS/TF/0519PTP

# Quick & Easy Installation!

FOR BOTH ENTRY & GARAGE DOOR FRAMES

### ONE 45° corner cut needed for entry door frames and single garage door frames

### None are needed for double garage door frames



1. Remove wood brickmould.



2. Measure door jamb & transfer dimensions to cladding.



3. Cut jamb cover & brickmould.

## **ENTRY DOOR KITS**

#### Sinale Door

Fits doors 36" wide x 80" high or smaller

Single Door with One Sidelight

Fits doors 36" wide & one 14" Sidelite x 80" high or smaller

#### Single Door with Two Sidelights

Fits doors 36" wide & two 14" Sidelite x 80" high or smaller

#### **Double Door**

Fits doors 36" wide x 80" high or smaller

## **OVERHEAD GARAGE DOOR KITS**

#### **Single Door**

Fits doors that are 9' wide x 8' high or smaller

#### Double Door


Fits doors that are 18' wide x 8' high or smaller

Note: all double doors have 2 piece headers •







4. Screw jamb covers to the jambs. 5. Snap on the new brickmould.



Measure the door and or sidelite only





## HOW TO ORDER YOUR DOOR FRAME

#### **Entry Door Frame**

- 1. Measure your entry door (and or sidelite if applicable)
  - Select the appropriate Entry Door Kit
- 2. Determine the current frame (jamb) width
  - 4-9/16" or 6-9/16"
- 3. Choose the color

### **Overhead Garage Door Frame**

- 1. Measure your garage door
  - Order aluminum frame by the garage door size
- 2. Determine if the current frame width is 5-1/2"
- Select frame style: 90° or 45° corners 3.
- Choose the color 4.

### **STANDARD COLORS:**





JAMB WIDTHS

Cladding is available in the standard widths shown below. It is also available in custom widths.

Jamb width may be increased by using jamb expanders. Details are at www.frontline.com

Maximum Jamb Widths:

Entry Door Frames - 12" Garage Door Frames - 10"